

WL Cube Firewall®

First class purification performance in a distinct compact unit

Excellent, thoroughly purified water for small workplaces

With its sophisticated and premium look, the WL Cube Firewall (WL Cube FW) is the ideal worktop solution for small working environments, meeting rooms, kitchens, bar and break areas.

Advanced technology

The WL Cube FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration.



Firewall

Waterlogic's patented Firewall technology features a highly effective UVC purification system at the point of dispense. Firewall guarantees 99.9999% purified water. Glass after glass.



BioCote® protection

The WL Cube FW key surfaces are infused with BioCote®, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odors, degradation of key surfaces and the potential for cross contamination.



Expert purification

Featuring Firewall, which thoroughly purifies the water as it is dispensed, acting also as a barrier preventing back contamination from outside, the WL Cube FW is the only compact machine on the market delivering totally safe and purified water, cleansed from pathogens by up to 99.9999%.

Features

Firewall, patented UV technology reduces the risks of bacteria, viruses, and cysts, purifying the water up to 99.9999%, 100% of the time

Removable drip tray to easily accommodate average size sport bottles

Elegant touch sensitive control panel for ease of use

Energy saving sleep mode to reduce power consumption when unit is not in use

LED UV fault indicator for easier servicing and peace of mind

BioCote® protected dispensing area

Technical specifications

Types available

Countertop

Dimensions

11.6" (W) x 14.8" (H) x 16.7" (D)

Dispensing area height

6.10" (with drip tray)

9.7" (without drip tray)

Weight

Standard model: ~39 lbs

Sparkling model: ~42 lbs

Standard filtration supplied

Carbon

Storage capacity

Cold tank: ~0.30 gal

Hot tank: ~0.28 gal

Water temperatures settings

Cold 41-59°F

Hot 188.6-203°F

Water options

cold



sparkling

ambient



hot



extra hot



Number of users



1 - 7



Tested and certified

NSF/ANSI-55 Class A
Ultraviolet Microbiological
Water Treatment Systems

NSF P231
Protocol for
Microbiological Purifiers



QUALITY & SAFETY
GUARANTEED

*certificate may vary depending on different model configuration

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Call us today

Waterlogic USA

Tel: 844 283 3514

100 Biddle Ave, Suite 203,
Newark, DE 19702

www.waterlogicsusa.com
info@waterlogicsusa.com

For more information, visit www.waterlogic.com