

WL270

Sturdy design and steady performance
for quality water



Reliable performance

Easy operation, robust design and durable materials, make the WL270 the perfect fit even for demanding environments. The gravity fed system makes this machine ideal for areas with low water pressure or situations where incoming water conditions require the use of reverse osmosis.

Advanced technology

The WL270 features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



In-tank UV sanitization

Waterlogic's in-tank UV technology acts against waterborne micro-organisms and bacteria, dispensing great quality water glass after glass.



BioCote® protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of potentially harmful bacteria, mold and fungi, and reduces the risk of cross-contamination.

Simply great, clear water

Free from chlorine (dependent on filters type and water conditions)

Free from waterborne tastes and odors

Free from bacteria

Features

Multiple filtration options to fit specific water conditions. A choice of carbon filtration or reverse osmosis, ideal to address poor incoming water conditions (including boil alerts)

Gravity-fed system, particularly suitable for low pressure installations, also guarantees water supply in case of power outage

The in-tank sanitizing system ensures water is exposed to the UV light to maintain the microbiological purity of the water

Faults indicators for easier servicing

BioCote® protected reservoir and dispensing area (including drip tray body, cold faucet, user interface panel and buttons)

Leak detection for peace of mind

Energy saving sleep mode

Water options

cold



sparkling

ambient



hot



extra hot

Technical specifications

Types available

Freestanding

Dimensions

14.9" (W) x 44.8" (H) x 13.3" (D)

Dispensing area height

9.4"

Weight

72.7 lbs

Standard filtration supplied

Reverse osmosis or 1 x Carbon filter

Storage capacity

Ambient reservoir: 2.5 gal

Cold tank: 1 gal

Total capacity: 4 gal

Hot tank (500 Watt): 1/2 gal

Compressor

110V (60 Hz)

Water temperature settings

Cold: 37 °F - 54 °F

Hot: 189 °F

Number of users



30 - 50

Tested and certified



CE QUALITY & SAFETY
GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Call us today

Waterlogic USA

Tel: 844 283 3514

100 Biddle Ave, Suite 203,
Newark, DE 19702

www.waterlogicusa.com
info@waterlogicusa.com

For more information, visit www.waterlogic.com