

WL380

Superior purification, proven performance and elegant design



The hydration station for the modern office

The WL380 by Waterlogic® brings a variety of refreshing purified water choices to the workplace, supplying cold, ambient, hot and extra hot options, and powered by Firewall®, Waterlogic's superior UV purification technology.

Advanced technology

The WL380 features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



Firewall

Waterlogic's patented Firewall technology features a highly effective UVC purification system at the point of dispense. Firewall guarantees 99.9999% purified water. Glass after glass.



BioCote® protection

The WL380 key surfaces are infused with BioCote®, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odors, degradation of key surfaces and the potential for cross contamination.

High performance purification system

WL380 is designed with a unique technology which delivers premium water, virtually bacteria free. In addition to that, the high performance filtration removes chlorine, lead and cysts to dramatically improve water quality and taste.

Features

Firewall, patented UV technology reduces the risks of bacteria, viruses, and pathogens purifying the water up to 99.9999%, 100% of the time

Touch sensitive control panel for easy operations

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

BioCote protected dispensing area

Water options

cold



sparkling

ambient



hot



extra hot



Number of users



15 - 30

Technical specifications

Types available

Freestanding

Dimensions

15.2" (W) x 45.3" (H) x 18.1"(D)

Dispensing area height

8.7"

Weight

66-75 lbs

Standard filtration supplied

Carbon

Storage capacity

Hot tank 0.53 US gal

Cold tank 1.06 US gal

Compressor

110/120v 60Hz

Water temperatures settings

Cold: 41°F

Hot: 189°F

Extra Hot: 199°F

Tested and certified

NSF/ANSI-55 Class A
Ultraviolet Microbiological
Water Treatment Systems
NSF P231
Protocol for
Microbiological Purifiers



CE QUALITY & SAFETY
GUARANTEED

*certificate may vary depending on different model configuration

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Call us today

Waterlogic USA

Tel: 844 283 3514

100 Biddle Ave, Suite 203,
Newark, DE 19702

www.waterlogicsusa.com
info@waterlogicsusa.com

For more information, visit www.waterlogic.com